



## Stauf Technical Information #3

### Approved Underlayments for Use with Stauf Adhesives

Stauf recommends using the #15 Stauf Trowel (3/32" x 3/32" x 3/32") for gluing down underlayment. Normal spread rate is up to 100 SF per gallon. See the pail for the proper size trowel to use when gluing the wood flooring to the underlayment.

#### **Name of Underlayment**

PROFLEX by Primary Acoustics  
Sound Solution by Healthier Choice  
"The Silencer by Foam Products Corp.  
Quiet-Core by Tarkett  
Insulayment by Midwest Padding, LLC  
PROFLEX 40CISM, 70SSC, 90MSC by Proflex Products, Inc.  
VERDEX by Smirnoff Building Systems  
QT3503 and QT 4002 by Dodge-Regupol  
QT 4005, QT4010, QT5015 by ecore, Inc.  
RB Rubber, 2mm & 6mm  
DinoFlex Rubber Underlayment  
AcoustiCork RC 1000  
NRT QD Max HB  
Cushion N Tred  
ProtectoWrap Whisper Mat-HW

#### **Approved for Five (5) Stauf Adhesives**

PUM-950 Power-Mastic (Urethane based)  
SMP-940 Superior (Polymer based)  
SMP-960 One-Step (Polymer based)  
WFR-930 Solva-Mastic\* (Alcohol based)  
CBR-970 Renovator (Polymer based)

#### **Name of Underlayment**

Sureflexx by US Rubber  
Quietdown Tile by National Rubber Technology  
Dura-Son Poly By Dura-Son  
Quit Sound II  
RB Rubber Athletic 'Rolled Rubber Flooring'  
NRT Quiet Down RC Acoustic Underlay  
NRT QD Granulated and NRT QD Max

#### **Approved for Four (4) Stauf Adhesives**

PUM-950 Power-Mastic (Urethane based)  
SMP-940 Superior (Polymer based)  
SMP-960 One-Step (Polymer based)  
CBR-970 Renovator (Polymer based)

#### **The following underlayment products were tested and are not approved for use with Stauf Adhesives:**

Diversified Floor Muffler  
VinylTrends EasyStep  
Sound Deadener  
New Dura-Son w/ Pe  
Acousti-Tech Membrane by Sinitec, Inc., Canada  
4# XLPE Solid Black MD and 2# XLPE Sound Barrier Select  
Konecto MSS-KD-200R  
Volara Foam

\*WFR-930 Solva-Mastic will typically dry more slowly and may create short term cupping due to non-absorbing properties of the various underlayments.

Visit the Stauf web site for more information or call Stauf Technical Services at 901.820.0007.

11-28-11

#### **STAUFL USA, LLC**

6055 Primacy Parkway, Suite 428  
Memphis, TN 38119

#### **Toll-Free: 1-866-GLUE USA**

Telephone: 1-901-820-0007  
Fax: 1-901-820-0101

#### **Internet & E-mail:**

www.staufusa.com  
info@staufusa.com