

Printing date 05/20/2016 Reviewed on 05/20/2016

1 Identification

· Product identifier

· Trade name: STAUF WFR-930

· Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Details of the supplier of the safety data sheet
- · Manufacturer:

STAUF Klebstoffwerk GmbH Oberhausener Strasse 1 57234 Wilnsdorf, Germany Phone 01149-273-930-1100 Fax 01149-273-930-1200

· Distributor:

STAUF USA, LLC. 11121 Hwy 70 Suite 102 Arlington, TN 38002, USA Phone 1-901-820-0007 Fax 1-901-820-0101

· Emergency telephone number: CHEMTREC 1-800-424-9300 (USA) 1-703-527-3887 (International)

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Flammable

Flammable.

Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Has a narcotizing effect.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Printing date 05/20/2016 Reviewed on 05/20/2016

Trade name: STAUF WFR-930

Hazard pictograms

(Contd. of page 1)





GHS02 GHS07

- · Signal word Danger
- Hazard statements

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P210

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P264 Wash thoroughly after handling.

P280 Wear protective gloves / eye protection / face protection.

Wear eye protection / face protection. P280

P303+P361+P353 IF ON ŚKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Classification system:

NFPA ratings (scale 0 - 4)



Health = 1Fire = 3Reactivity = 0

· WHMIS-ratings (scale 0 - 4)



Health = 1Fire = 3REACTIVITY 0 Reactivity = 0

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
	Distillates (petroleum), steam cracked, polymers with acidtreated coal solvent naphtha and phenol	10-25%	
79-20-9	methyl acetate	2.5-10%	
67-64-1	acetone	2.5-10%	
1332-58-7	Kaolin	2.5-10%	
64-17-5		2.5-10%	

(Contd. on page 3)



Printing date 05/20/2016 Reviewed on 05/20/2016

Trade name: STAUF WFR-930

(Contd. of page 2)

27138-31-4 Dipropylenglycol dibenzoat

≤ 2.5%

· Additional information: For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air: consult doctor in case of complications.
- · After skin contact: Generally the product does not irritate the skin.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- US



Printing date 05/20/2016 Reviewed on 05/20/2016

Trade name: STAUF WFR-930

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Prevent impact and friction.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components	with limi	t values t	that require	monitoring:	at the workplace:
COMPONENIS	441611 111111	ı valu c ə i	ınaı redune	IIIOIIIIOI IIIO	al life workblace.

79-20-9 methyl acetate

PEL Long-term value: 610 mg/m³, 200 ppm

REL Short-term value: 760 mg/m³, 250 ppm

Long-term value: 610 mg/m³, 200 ppm

TLV Short-term value: 757 mg/m³, 250 ppm Long-term value: 606 mg/m³, 200 ppm

67-64-1 acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm

BEI

1332-58-7 Kaolin

PEL Long-term value: 15* 5** mg/m³

*total dust **respirable fraction

REL Long-term value: 10* 5** mg/m³

*total dust **respirable fraction

TLV Long-term value: 2* mg/m³ E; as respirable fraction

64-17-5 ethanol

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1880 mg/m³, 1000 ppm

(Contd. on page 5)



Printing date 05/20/2016 Reviewed on 05/20/2016

Trade name: STAUF WFR-930

(Contd. of page 4)

· Ingredients with biological limit values:

67-64-1 acetone

BEI 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Breathing equipment:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

- · Protection of hands: Not required.
- · Material of gloves Butyl rubber, BR
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid Color: Beige · Odor: Solvent-like · Odour threshold: Not determined.

· pH-value at 20 °C (68 °F): 7

· Change in condition

Boiling point/Boiling range: 55 °C (131 °F) -19 °C (-2 °F) · Flash point: · Flammability (solid, gaseous): Not applicable. · Ignition temperature: 425 °C (797 °F) · Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

(Contd. on page 6)



Printing date 05/20/2016 Reviewed on 05/20/2016

Trade name: STAUF WFR-930

(Contd. of page 5)

• Danger of explosion: Product is not explosive. However, formation of explosive air/

vapor mixtures are possible.

· Explosion limits:

Lower: 3.1 Vol % *Upper:* 16.0 Vol %

Vapor pressure at 20 °C (68 °F): 220 hPa (165 mm Hg)
 Density at 20 °C (68 °F): 1.5 g/cm³ (12.518 lbs/gal)

Relative density
Vapour density
Evaporation rate
Not determined.
Not determined.
Not determined.

· Solubility in / Miscibility with

Water: Partly miscible.Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic at 20 $^{\circ}$ C (68 $^{\circ}$ F): 69100 mPas Kinematic: Not determined.

· Solvent content:

Organic solvents: 21.4 % Water: 1.3 % VOC Content: 5.1 %

SCAQMD Rule 1168: 89 g/L (calculated)

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50	· LD/LC50 values that are relevant for classification:				
Distillates (petroleum), steam cracked, polymers with acidtreated coal solvent naphtha and phenol					
Oral	LD50	> 16000 mg/kg (rat)			
79-20-9 r	79-20-9 methyl acetate				
Oral	LD50	6970 mg/kg (rat)			
67-64-1 a	67-64-1 acetone				
Oral	LD50	5800 mg/kg (rat)			
Dermal	LD50	20000 mg/kg (Ratte)			

(Contd. on page 7)



Printing date 05/20/2016 Reviewed on 05/20/2016

Trade name: STAUF WFR-930

				(Contd. of page 6)
ſ	Inhalative	LC50/48 h	76 mg/l (rat)	
Ī	64-17-5 et	hanol		
Ī	Oral	LD50	5560 mg/kg (mee)	
			3450 mg/kg (mou)	
			7060 mg/kg (rat)	
			6300 mg/kg (rabbit)	
	Inhalative	LC50/48 h	20000 mg/l (rat)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:
- · Carcinogenic categories

· Carcinogenic categories		
,	rnational Agency for Research on Cancer)	
9003-20-7	Polyvinylacetat	3
64-17-5	ethanol	1
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- **Recommendation:** If product has aged or solidified conventional means of disposal are acceptable.
- · Uncleaned packagings:
- · **Recommendation:** Disposal must be made according to official regulations.

- US



Printing date 05/20/2016 Reviewed on 05/20/2016

Trade name: STAUF WFR-930

(Contd. of page 7)

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA UN1133

· UN proper shipping name

· DOT Adhesives

· ADR 1133 Adhesives, special provision 640H

· IMDG, IATA **ADHESIVES**

Transport hazard class(es)

· DOT



· Class 3 Flammable liquids

· Label

· ADR, IMDG, IATA



· Class 3 Flammable liquids

· Label

· Packing group

· DOT, ADR, IMDG, IATA Ш

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

· Danger code (Kemler): 33 · EMS Number: F-E,S-D

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

·IMDG

5L · Limited quantities (LQ) Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN1133, Adhesives, special provision 640H, 3, III

(Contd. on page 9)



Printing date 05/20/2016 Reviewed on 05/20/2016

Trade name: STAUF WFR-930

(Contd. of page 8)

	(Contd. of page
5 Regulatory information	
· Safety, health and environmental regulations/legislation specific for the substa	ance or mixture
· Sara	
· Section 355 (extremely hazardous substances):	
None of the ingredient is listed.	
· Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
64-17-5 ethanol	
· Canadian Ingredient disclosure list	
· Limit 0,1%	
64-17-5 ethanol	
· Limit 1%	
79-20-9 methyl acetate	
67-64-1 acetone	
· Cancerogenity categories	
· EPA (Environmental Protection Agency)	
67-64-1 acetone	
· TLV (Threshold Limit Value established by ACGIH)	
67-64-1 acetone	A
1332-58-7 Kaolin	A
64-17-5 ethanol	A
· MAK (German Maximum Workplace Concentration)	
64-17-5 ethanol	
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
5	

· National regulations:

· Technical instructions (air):

Class	Share in %
Wasser	≤ 2,5
NK	10-25

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 05/20/2016 Reviewed on 05/20/2016

Trade name: STAUF WFR-930

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Department
- Contact:

Dr. Frank Gahlmann +49-(0)2739-301165 gahlmann@stauf.de

Wolfgang Stauf, Phone 901-820-0007, Email wolfgang.stauf@staufusa.com

- · Date of preparation / last revision 05/20/2016 / 24
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

. . .