

Page 1/9

# Safety Data Sheet acc. to OSHA HCS

Printing date 03/22/2018 Reviewed on 03/22/2018

#### 1 Identification

· Product identifier

Trade name: CTS-837

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: STAUF USA, LLC.

11121 Hwy 70 Ste 102 ARLINGTON, TN 38002 +1 (866) 458-3872

· Emergency telephone number:

CHEMTREC USA +1 (800) 424-9300 & INTERNATIONAL +1 (703) 527-3887

# 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS08

- · Signal word Warning
- · Hazard-determining components of labeling:

1,2-benzisothiazol-3(2H)-one ethyl acrylate

Hazard statements

May cause an allergic skin reaction.

Suspected of causing cancer.

**Precautionary statements** 

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 2)

(Contd. of page 1)

# Safety Data Sheet acc. to OSHA HCS

Printing date 03/22/2018 Reviewed on 03/22/2018

Trade name: CTS-837

If on skin: Wash with plenty of water.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:
- NFPA ratings (scale 0 4)



Health = 0 Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 0 Fire = 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
1332-58-7	Kaolin	22.48%
140-88-5	ethyl acrylate	0.836%
2634-33-5	1,2-benzisothiazol-3(2H)-one	0.08%

## 4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- $^{\cdot}$  Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

JS -

Printing date 03/22/2018 Reviewed on 03/22/2018

Trade name: CTS-837

(Contd. of page 2)

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

## 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**Protective Action Criteria for Chemicals** 

· PAC-1:		
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic 140 mg/	
140-88-5	5 ethyl acrylate 8.3 ppm	
57-13-6	urea	30 mg/m <sup>3</sup>
9016-45-9	9 nonylphenolethoxylates	
· PAC-2:		
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic	1,500 mg/m <sup>3</sup>
140-88-5	ethyl acrylate	36 ppm
57-13-6	urea	280 mg/m <sup>3</sup>
9016-45-9	nonylphenolethoxylates 470 mg/r	
· PAC-3:		
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic 8,90	
140-88-5	ethyl acrylate	240 ppm
57-13-6	urea	1,700 mg/m <sup>3</sup>
9016-45-9	5-9 nonylphenolethoxylates 5,400 mg/m³	

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 4)

Printing date 03/22/2018 Reviewed on 03/22/2018

Trade name: CTS-837

(Contd. of page 3)

- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

### 1332-58-7 Kaolin

PEL Long-term value: 15\* 5\*\* mg/m³

\*total dust \*\*respirable fraction

REL Long-term value: 10\* 5\*\* mg/m³

\*total dust \*\*respirable fraction

FLV Long-term value: 2\* mg/m³ E; as respirable fraction

### 140-88-5 ethyl acrylate

PEL Long-term value: 100 mg/m<sup>3</sup>, 25 ppm

Skin

REL See Pocket Guide App. A

TLV Short-term value: 61 mg/m³, 15 ppm Long-term value: 20 mg/m³, 5 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- · Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 03/22/2018 Reviewed on 03/22/2018

Trade name: CTS-837

(Contd. of page 4)

• Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical prope	erties
· Information on basic physical and	chemical properties
· General Information	
· Appearance:	
Form:	Fluid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	100 °C (212 °F)
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible.
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Water:	26.3 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gl
· Other information	No further relevant information available.

Printing date 03/22/2018 Reviewed on 03/22/2018

Trade name: CTS-837

(Contd. of page 5)

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:			
140-88-5	140-88-5 ethyl acrylate		
Oral	LD50	800 mg/kg (rat)	
Dermal	LD50	1,834 mg/kg (rabbit)	

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

Inhalative LC50/4 h 2,180 mg/l (rat)

The product shows the following dangers according to internally approved calculation methods for preparations:

İrritant

Carcinogenic categories

· IARC	(Internationa	I Agency for	Research o	n Cancer)
--------	---------------	--------------	------------	-----------

140-88-5 ethyl acrylate

2B

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

(Contd. on page 7)

Printing date 03/22/2018 Reviewed on 03/22/2018

Trade name: CTS-837

(Contd. of page 6)

Danger to drinking water if even extremely small quantities leak into the ground.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information	
· UN-Number · DOT, IMDG, IATA	not regulated
· UN proper shipping name · DOT, IMDG, IATA	not regulated
· Transport hazard class(es)	
· DOT, IMDG, IATA · Class	not regulated
· Packing group · DOT, IMDG, IATA	not regulated
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	x II of Not applicable.
· UN "Model Regulation":	not regulated

# 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· TSCA (Toxi	c Substances Control Act):
1332-58-7	Kaolin
	Petroleum Hydrocarbon Resin
64742-52-5	Distillates (petroleum), hydrotreated heavy naphthenic
	ethyl acrylate
57-13-6	urea
9016-45-9	nonylphenolethoxylates

(Contd. on page 8)

Printing date 03/22/2018 Reviewed on 03/22/2018

Trade name: CTS-837

(Contd. of page 7) 2634-33-5 1,2-benzisothiazol-3(2H)-one 7732-18-5 water, distilled, conductivity or of similar purity TSCA new (21st Century Act) (Substances not listed) · Proposition 65 · Chemicals known to cause cancer: 140-88-5 ethyl acrylate · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. Carcinogenic categories EPA (Environmental Protection Agency) 57-13-6 urea Ш TLV (Threshold Limit Value established by ACGIH) 1332-58-7 Kaolin Α4 140-88-5 ethyl acrylate Α4 · NIOSH-Ca (National Institute for Occupational Safety and Health)

## GHS label elements

140-88-5 ethyl acrylate

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07 GHS08

#### · Signal word Warning

#### · Hazard-determining components of labeling:

1,2-benzisothiazol-3(2H)-one

ethyl acrylate

#### · Hazard statements

May cause an allergic skin reaction.

Suspected of causing cancer.

### **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 9)

Printing date 03/22/2018 Reviewed on 03/22/2018

Trade name: CTS-837

(Contd. of page 8)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Department
- · Contact: Technical Director
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

US